

Panasonic
ideas for life

Surveillance Cameras

**OUR PROMOTIONAL OFFERS, SELECTED UNITS ONLY AVAILABLE,
WHILE STOCK LASTS.**

CALL US AT 6282-0555 or FAX IN AT 6281-0555 TODAY

BB-HCM311

IPv4/v6 Audio 2-way Type
Indoor Network Camera

**STAR
BUY**



▲ IPv6 Ready Logo*1



GREAT FEATURES TO BE EXPLORED

BB-HCM311

Network Camera

Multi-Camera Setup Supported

New CCD Sensor Enhances Image Expression

Standard SD Memory Card Slot

Two-Way Voice Communications Supported

IPv6-Ready

IPsec** Supported

Alarm-Controlled and Timer-Controlled
Image Transfer Functions

A Wide Range of Camera Control Functions

**OUR PROMOTIONAL OFFERS, SELECTED UNITS ONLY AVAILABLE,
WHILE STOCK LASTS.**

CALL US AT 6282-0555 or FAX IN AT 6281-0555 TODAY

ACM-3111

SuperCMOS IP Dome Camera with IR Option

Specifications

- Superior low-light performance down to 0.1 Lux
- Build in 3.8 mm fixed lens
- Build in IR LED and CDS sensor (ACM-3111)
- MPEG-4 / MJPEG compression supported
- CIF up to VGA resolution at 30/25 FPS
- Two way audio supported
- Power over Ethernet (IEEE 802.3af) supported (ACM-3111)



ACM-3311

IP IR 3-inch Dome Camera

Specifications

- 1/3" Sony SuperHAD CCD
- Integrated f4.3 mm / F2.0 Lens
- 0 Lux (IR LED ON)
- Backlight Compensation, Auto White Balance supported
- Selectable MPEG-4 / MJPEG compression
- CIF up to Full D1 resolution at 30/25 FPS
- Multi-stream with variable frame rate in the same compression
- Two-way audio supported
- Hardware motion detection
- Hybrid analog and ethernet video output with 420 TV lines
- Power over Ethernet (IEEE 802.3af) supported
- Surface and wall mount supported

